



Product Comparator

Simply tick up to 3 product boxes to view a side-by-side product comparison.



Where to buy ►



Where to buy ►



Where to buy ►

PRINTER FUNCTIONS

Print Resolution :	Up to 9600 x 2400 dpi •	Up to 9600 x 2400 dpi •	Up to 4800 x 1200 dpi
Print Engine :	5-ink FINE print head with 1 pl Micro-Nozzles	5-ink FINE print head with 1 pl Micro-Nozzles	5-ink with Micro-Nozzles, FINE, 2 pl ContrastPLUS
Colour management :			ICM, ColorSync, Exif Print
Photo Lab Quality Speed :	Borderless 10 x 15cm: Approx. 51 seconds (Std)	Borderless 10 x 15cm: Approx. 36 seconds (Std)	
Mono Print Speed :	Up to 29ppm (Max.), 14.7ppm (Std)	Up to 30ppm (Max.), 15ppm (Std)	Up to 25 ppm (Max), 15 ppm (Std)
Colour Print Speed :	Text Graphics: Up to 19ppm (Max.), 10.7ppm (Std) A4 Full Page: Approx. 25 seconds (Std)	Text Graphics: Up to 24ppm (Max.), 11.7ppm (Std) A4 Full Page: Approx. 19 seconds (Std)	Text Graphics: Up to 17 ppm (Max), 11 ppm (Std); A4 Full Page: Up to 2.3 ppm (Std)
Photo print speed :			A4: Up to 0.86 ppm (Max) Borderless 10 x 15 cm: approx 36 seconds (Max)
Ink Cartridge Configuration :	Single Ink technology - 5 separate ink tanks (PGI-5BK, CLI-8BK, CLI-8C, CLI-8M CLI-8Y)	Single Ink technology - 5 separate ink tanks (PGI-5BK, CLI-8BK, CLI-8C, CLI-8M CLI-8Y)	
Black Ink Tank Life :	PGI-5BK: 360 pages at 5% coverage • PGI-5BK: 1450 pages (Printing ISO/JIS-SCID N5) ²	PGI-5BK: 360 pages at 5 % coverage • PGI-5BK: 1250 pages (Printing ISO/JIS-SCID N5) ²	
Colour Ink Tank Life :	490 pages at 5% coverage per ink tank • Cyan: 850 pages, Magenta: 600 pages, Yellow: 540 pages, (Printing ISO/JIS-SCID N5) •	420 pages at 5% coverage per ink tank • Cyan: 710 pages, Magenta: 500 pages, Yellow: 480 pages, (Printing ISO/JIS-SCID N5) •	

Media Type :	Plain Paper, Envelopes, Photo Paper Pro (PR-101), Photo Paper Plus Glossy (PP-101), Photo Paper Plus Double Sided (PP-101D), Photo Paper Plus Semi-gloss (SG-101), Glossy Photo Paper (GP-401), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), Transparency (CF-102), T-shirt Transfer (TR-301), Photo Stickers (PS-101), Super White Paper (SW-201)	Plain Paper, Envelopes, Photo Paper Pro (PR-101), Photo Paper Plus Glossy (PP-101), Photo Paper Plus Double Sided (PP-101D), Photo Paper Plus Semi-gloss (SG-101), Glossy Photo Paper (GP-401), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), Transparency (CF-102), T-shirt Transfer (TR-301), Photo Stickers (PS-101), Super White Paper (SW-201)	Plain Paper, Envelopes, Photo Paper Pro (PR-101), Photo Paper Plus Glossy (PP-101), Photo Paper Plus Double Sided (PP-101D), Photo Paper Plus Semi-gloss (SG-101), Glossy Photo Paper (GP-401), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), Transparency (CF-102), T-shirt Transfer (TR-301), Photo Stickers (PS-101)
Paper weight :			Sheet feeder: 64 to 105 g/m ² and supported. Canon special media up to 273 g/m ²
Media Input :	Sheet feeder: Approx. 150 sheets Cassette: Approx. 150 sheets DVD/CD tray: 1 printable DVD or CD	Sheet feeder: Approx. 150 sheets Cassette: Approx. 150 sheets DVD/CD tray: 1 printable DVD or CD	Sheet feeder: 150 sheets; Cassette: 150 sheets; CD-R / DVD tray: 1 printable CD-R or DVD
CD-R printing :			Available as standard
Media Size :	Sheet feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, Credit Card (54 x 86mm) Cassette: A4, B5, A5, Letter, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm	Sheet feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, Credit Card (54 x 86mm) Cassette: A4, B5, A5, Letter, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm	Sheet feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15 cm, 13 x 18 cm, Credit Card (54 x 86 mm) Cassette: A4, B5, A5, Letter, Envelopes (DL size or Commercial 10), 10 x 15 cm, 13 x 18 cm
Media Weight :	Sheet feeder/Cassette: 64 to 105 g/m ² and supported Canon special media up to 273 g/m ²	Sheet feeder/Cassette: 64 to 105 g/m ² and supported Canon special media up to 273 g/m ²	
DVD/CD Printing :	Available as standard	Available as standard	
Two Sided Printing :	Automatically selectable using Photo Paper Plus Double Sided, Super White Paper or plain paper in A4, B5, A5, Letter 13 x 18cm sizes	Automatically selectable using Photo Paper Plus Double Sided, Super White Paper or plain paper in A4, B5, A5, Letter 13 x 18cm sizes	
Borderless printing :	Available using Photo Paper Pro (A4 10 x 15cm), Photo Paper Plus Glossy (A4, 10 x 15cm, 13 x 18cm), Photo Paper Plus Semi Gloss (A4 10 x 15cm), Glossy Photo Paper (A4, 10 x 15cm Credit Card), Matte Photo Paper (A4, 10 x 15cm)	Available using Photo Paper Pro (A4 10 x 15cm), Photo Paper Plus Glossy (A4, 10 x 15cm, 13 x 18cm), Photo Paper Plus Semi Gloss (A4 10 x 15cm), Glossy Photo Paper (A4, 10 x 15cm Credit Card), Matte Photo Paper (A4, 10 x 15cm)	Available using Photo Paper Pro, Photo Paper Plus Glossy, Photo Paper Plus Double Sided, Photo Paper Plus Semi-gloss, Glossy Photo Paper or Matte Photo Paper in A4, 10 x 15 cm, 13 x 18 cm Credit Card sizes
Duplex printing :			Available using Photo Paper Plus Double Sided or plain paper in A4, B5, A5, Letter 13 x 18 cm sizes
Cartridge configuration :			Single Ink technology - five separate ink tanks (BCI-3eBK, BCI-6BK, BCI-6C, BCI-6M, BCI-6Y)

Black cartridge life :				BCI-3eBK: 330 pages at 5% coverage•; BCI-6BK: 440 pages at 5% coverage ² BCI-3eBK: 1500 pages, BCI-6BK: 2000 pages (Printing ISO/JIS-SCID N5) ²
Colour cartridge (s) life :				440 pages at 5% coverage per ink tank• Cyan: 550 pages, Magenta: 430 pages, Yellow: 360 pages (Printing ISO/JIS-SCID N5)•
INTERFACE AND CONNECTIVITY				
Interface Type - PC :	USB 2.0 Hi-Speed •		USB 2.0 Hi-Speed •	Parallel (IEEE 1284 compatible) USB
Interface Type - Camera :	Direct Print Port: Camera direct photo printing from PictBridge and Bubble Jet Direct compliant digital cameras and camcorders		Direct Print Port: Camera direct photo printing from PictBridge and Bubble Jet Direct compliant digital cameras and camcorders	Direct Print Port; Camera direct photo printing from PictBridge Bubble Jet Direct compliant digital cameras camcorders
Camera Direct Printing :	Compatibility: Exif 2.2 or earlier, DPOF compliant		Compatibility: Exif 2.2 or earlier, DPOF compliant	Compatibility: Exif 2.2 or earlier, DPOF compliant
DRIVERS AND SOFTWARE				
Operating System Requirements :	Windows: PC with Windows XP, Windows 2000, Windows Me or Windows 98, USB interface •, CD-ROM Drive. Free hard disk space: 370 MB for Windows XP/2000 and Windows Me/98. Mac: Macintosh computer with Mac OS X v10.2.1 or later, USB interface. Free hard disk space: 350 MB for Mac OS X v10.2.1 or later.		Windows: PC with Windows XP, Windows 2000, Windows Me or Windows 98, USB interface •, CD-ROM Drive. Free hard disk space: 370 MB for Windows XP/2000 and Windows Me/98. Mac: Macintosh computer with Mac OS X v10.2.1 or later, USB interface. Free hard disk space: 350 MB for Mac OS X v10.2.1 or later.	Windows: PC with Windows XP, Windows 2000, Windows NT 4.0, Windows Me, Windows 98 or Windows 95, USB interface•, CD-ROM Drive. Free hard disk space: 50 MB for Windows XP/2000/NT 4.0, 15 MB for Windows Me/98/95. Mac: Macintosh computer with Mac OS 9.x or Mac OS X v10.2.1 or later, USB interface. Free hard disk space: 30 MB for Mac OS 9.x, 100 MB for Mac OS X v10.2.1 or later.
Driver Features :	Windows: Photo Optimizer PRO, Image Optimizer, Photo Noise Reduction, Vivid Photo Mac: Photo Optimizer PRO, Vivid Photo, Photo Noise Reduction		Windows: Photo Optimizer PRO, Image Optimizer, Photo Noise Reduction, Vivid Photo Mac: Photo Optimizer PRO, Vivid Photo, Photo Noise Reduction	Windows: Photo Optimizer PRO, Image Optimizer, Photo Noise Reduction, Vivid Photo Mac OS 9.x: Photo Optimizer PRO, Vivid Photo, Photo Noise Reduction, Vivid Photo Mac OS X: Photo Noise Reduction, Vivid Photo
Software Included :	Windows: Easy-WebPrint, Easy-PhotoPrint, PhotoRecord, Easy-PrintToolBox, CD-LabelPrint Mac: Easy-PhotoPrint, CD-LabelPrint		Windows: Easy-WebPrint, Easy-PhotoPrint, PhotoRecord, Easy-PrintToolBox, CD-LabelPrint Mac: Easy-PhotoPrint, CD-LabelPrint	Windows: Easy-WebPrint, Easy-PhotoPrint, PhotoRecord, Easy-PrintToolBox, CD-LabelPrint Mac: Easy-PhotoPrint, CD-LabelPrint
GENERAL FEATURES				
Power Source :	AC 100-240V 50/60Hz		AC 220-240V 50/60Hz	AC 220-240 V 50/60 Hz
Power Consumption :	Approx. 0.8W (standby), approx. 17W (printing)		Approx. 0.8W (standby), approx. 17W (printing)	Approx. 0.5 W (standby), approx. 16 W (printing)
Temperature range :	5° - 35° C		5° - 35° C	5 - 35 °C
Humidity :	10 - 90% RH (no condensation)		10 - 90% RH (no condensation)	10 - 90% RH (no condensation)

Acoustic noise levels :	Approx. 34.2dB (A) (best quality mode)	Approx. 34.7dB (A) (best quality mode)	Approx. 35 dB (A) in the best quality mode
Dimensions (W x D x H) :	419 x 299 x 160mm	444 x 309 x 160mm	418 x 286 x 170 mm
Weight :	Approx. 6.5kg	Approx. 7.3kg	Approx. 6.7 kg

CLOSE